

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Date

Application  
Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M2611

051712254106

233 mm

66 mm

140 mm

216 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

78 mm

No

AC

50 A

DIN 43653 /80 Visual indicator

Other

00

690 V (IEC)

Top fuse status indicator

640 at 660 V

690 V

None

Blade end x blade end

M10

gR (general purpose semiconductor protection)

10 W

Fuse

Square body, slotted offset bolted tags

200 kA

Class gR

95

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Standard