

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Compliances

产品规格

Certifications  
Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Rated switching capacity  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

Date

Mon Oct 23 2023

Eaton Bussmann series high speed traction fuse

170M2100

051712771016

164 mm

66 mm

39 mm

0.001 g

CE RoHS Compliant EAC

IEC 60269-4

1200 V

50 kAIC

139.5 mm

DC

Other

20 A

62 Hz

150 A

Single slot tags

1\*

249 at 1200 Vdc

None

Ceramic

M8

aR (accompanied semiconductor protection)

2 W

Fuse

Square body, offset bolted tags

100 kA

45 Hz

Class aR

82

traction third rail

Standard