

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight

产品规格

Compliances  
Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Rated switching capacity  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I<sup>2</sup>T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I<sup>2</sup>T)  
Application  
Voltage type  
Packaging type  
Mon Oct 23 2023

Date

Eaton Bussmann series high speed traction fuse

170M2102

051712770989

164 mm

66 mm

39 mm

823.333 g

CE

1200 V

50 kAIC

139.5 mm

DC

Other

32 A

62 Hz

150 A

Single slot tags

1\*

994 at 1200 Vdc

None

Ceramic

M8

aR (accompanied semiconductor protection)

9 W

Fuse

Square body, offset bolted tags

100 kA

45 Hz

Class aR

327

traction third rail

Standard