

**常用规格**

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications  
Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Rated switching capacity  
Fuse size  
Voltage rating  
Fuse indicator  
Special features  
Construction size  
Clearing (I2T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

**产品规格**

**Date**

Mon Oct 23 2023

Eaton Bussmann series high speed traction fuse

170M2018

051712391399

150 mm

92 mm

161 mm

4592 g

Not Applicable

IEC

750 V

110 kAIC

148 mm

DC

Other

1250 A

62 Hz

110 A

23

Parallel Fuse Link

3

2875800 at 750 Vdc

None

Ceramic

gR (general purpose semiconductor protection)

224 W

Fuse

Square body, parallel bolted tags

110 kA

45 Hz

Class gR

694000

traction third rail

Standard