

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Clearing loss
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3220

051712255271

290 mm

62 mm

142 mm

0.311 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

65

108 mm

No

AC

450 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

690 V (IEC), 700 V (UL)

Top fuse status indicator

140000 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

65 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

21000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard