

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Clearing loss
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3268

051712799805

305 mm

65 mm

145 mm

340.5 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

55

106 mm

No

AC

DIN 43 620

350 A

Bolted tag DIN 43653

Other

1*

690 V

Centre fuse status indicator

68500 at 660 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

55 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

10000

semiconductor protection

Standard