

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3565

051712256568

193 mm

47 mm

106 mm

262 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

50 mm

No

AC

Flush

200 A

Flush end GKN/Type K indicator for micro

IEC 60269-4 flush end connections type A

1*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

Other

15000 at 660 V

690 V

None

aR (accompanied semiconductor protection)

35 W

Fuse

Square body, flush end contacts

200 kA

Class aR

2200

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard