

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3618

051712799089

305 mm

65 mm

145 mm

319 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

78.5 mm

No

AC

350 A

US Style FU/Without indicator Bolted tag

Other

1*

690 V

None

68500 at 660 V

Blade end x blade end

M10

aR (accompanied semiconductor protection)

55 W

Fuse

Square body, center bolted tags

200 kA

Class aR

10000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard