

**常用规格**

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances

**产品规格**

Certifications  
Interrupt rating  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

**Date**

Application  
Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3815D

051712334037

135 mm

64 mm

40 mm

418.8333333 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

No

AC

200 A

DIN 43620 Bladed

Other

Dual indicator

1

690 V (IEC), 700 V (UL)

Combination fuse status indicator

16500 at 660 V

690 V

None

Din 43-620 blade end x Din 43-620 blade end

aR (accompanied semiconductor protection)

12.5 W

Fuse

Square body, knife blade contacts

200 kA

Class aR

2300

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard