

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application

Date

Voltage type  
Packaging type  
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse  
170M3467  
051712799980  
60 mm  
50 mm  
43 mm  
264 g  
Not Applicable  
CE Marked RoHS Compliant  
UL Recognized IEC Rated  
200 kAIC

No  
AC  
Flush  
315 A  
Flush end BKN/Type K Indicator for Micro  
IEC 60269-4 flush end connections type A  
Type K Indicator for micro  
1\*  
690 V (IEC), 700 V (UL)  
Centre fuse status indicator  
Other  
46500 at 660 V  
690 V  
None  
M8  
aR (accompanied semiconductor protection)  
50 W  
Fuse  
Square body, flush end contacts  
200 kA  
Class aR  
7000  
Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers  
  
Standard