

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of
connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

产品规格

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M3764

051712816724

92 mm

60 mm

163 mm

176 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

117 mm

No

AC

160 A

US Style FKE/115 Type K indicator for micro

Bolted tag

Other

Type K Indicator for micro

1*

690 V

Centre fuse status indicator

7500 at 660 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, center bolted tags

200 kA

Class aR

1100

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard