

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances

产品规格

Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3658

051712793049

305 mm

65 mm

145 mm

319 g

RoHS Compliant EAC CE

IEC 60269-4

200 kAIC

78.5 mm

No

AC

40 A

US Style FKE/Type K indicator for micro

Other

Type K Indicator for micro

1*

690 V

Top fuse status indicator

270 at 660V

None

M10

aR (accompanied semiconductor protection)

9 W

Fuse

Square body, center bolted tags

200 kA

Class aR

40

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard