

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3569

051712792769

193 mm

47 mm

106 mm

263 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

50 mm

No

AC

Flush

400 A

Flush end GKN/Type K indicator for micro

Other

1*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

105000 at 660 V

690 V

None

aR (accompanied semiconductor protection)

60 W

Fuse

200 kA

Class aR

77

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard