

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty

产品规格

Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Date

Application  
Voltage type  
Packaging type  
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3561

051712256520

193 mm

47 mm

106 mm

267 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

50 mm

No

AC

Flush

80 A

Flush end GKN/Type K indicator for micro

Other

1\*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

1250 at 660 V

690 V

None

aR (accompanied semiconductor protection)

18 W

Fuse

Square body, flush end contacts

200 kA

Class aR

185

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard