

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse
170M3471
051712256223
60 mm
50 mm
43 mm
44.3 g
Not Applicable
CE Marked
IEC Rated UL Recognized
200 kAIC

No
AC
Flush
500 A
Flush end BKN/Type K Indicator for Micro
IEC 60269-4 flush end connections type A
Type K Indicator for micro
1*
690 V (IEC), 700 V (UL)
Centre fuse status indicator
Other
180000 at 660 V
690 V
None
M8
aR (accompanied semiconductor protection)
70 W
Fuse
Square body, flush end contacts
200 kA
Class aR
185
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard