

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3695

051712256872

156 mm

59 mm

45 mm

431 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized CSA Certified

100 kAIC

116 mm

No

AC

250 A

US Style FU/115 without indicator Bolted tag

Other

1*

1250 V

None

54500 at 1000 V, 73000 at 1250 V

M10

aR (accompanied semiconductor protection)

55 W

Fuse

Square body, center bolted tags

100 kA

Class aR

9200

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

AC/DC

Standard