

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty

产品规格

Compliances
Certifications
Interrupt rating
Center-to-center distance of
connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application

Voltage type
Packaging type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M3241

051712255349

305 mm

65 mm

145 mm

59.667 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

100 kAIC

106 mm

No

AC

100 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

4450 at 1000 V, 5950 at 1250 V

1250 V

None

M10

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, slotted center bolted tags

100 kA

Class aR

750

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard