常用规格

产品规格

Product Name Catalog Number

UPC

Product Length/Depth

Product Height Product Width Product Weight

Warranty Compliances Certifications Interrupt rating

Center-to-center distance of

connections

Insulated metal gripping lugs (IMGL)

Current type Amperage Rating Fuse type

Fuse system (according to IEC 60269)

Fuse size Voltage rating Fuse indicator Construction size Clearing (I2T) Rated voltage AC

Color Connection

Mounting dimension Utilization category

Watt losses

Туре

Fuse shape

Breaking capacity

Class

Pre arc (I2T)

Application

Voltage type Packaging type Thu Oct 26 2023

Date

```
Eaton Bussmann series high speed square body fuse
170M3611
051712256650
305 mm
65 mm
145 \text{ mm}
319 g
Not Applicable
CE Marked RoHS Compliant
UL Recognized IEC Rated
200 kAIC
78.5 mm
No
AC
80 A
US Style FU/Without indicator Bolted tag
1*
690 V
None
1250 at 660 V
Blade end x blade end
M10
aR (accompanied semiconductor protection)
18 W
Fuse
Square body, center bolted tags
200 kA
Class aR
185
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers
```

 ${\tt Standard}$