常用规格

产品规格

Product Name Catalog Number

UPC

Product Length/Depth

Product Height Product Width Product Weight

Warranty Compliances Certifications Interrupt rating

Center-to-center distance of

connections

Insulated metal gripping lugs (IMGL)

Current type Amperage Rating

Fuse type

Fuse system (according to IEC 60269)

Fuse size Voltage rating Fuse indicator Construction size Clearing (I2T) Rated voltage AC

Color

Mounting dimension Utilization category

Watt losses

Type

Fuse shape

Breaking capacity

Class

Pre arc (I2T)

Application

Voltage type Packaging type Thu Oct 26 2023

Date

```
Eaton Bussmann series high speed square body fuse
170M3968
051712678902
290 mm
62 mm
142 \text{ mm}
0.001 g
Not Applicable
CE Marked RoHS Compliant
IEC Rated UL Recognized
125 kAIC
106 mm
No
AC
100 A
DIN 43653 KN/110 Type K Indicator for Micro
1*
1000 V (IEC)
Centre fuse status indicator
5100 at 1000 V
1000 V
None
M10
aR (accompanied semiconductor protection)
35 W
Fuse
Square body, slotted center bolted tags
125 kA
Class aR
860
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers
```

Standard